

Valtek ShearStream Segmented Ball Valve Series



Experience In Motion






Valtek ShearStream

Effective control for demanding flows. After more than one hundred years of close cooperation with our customers, we at Flowserve know what it is all about. Our robust valve and actuators, together with our advanced positioners, are designed to cope with the demands and control of all types of flowing media. With the focus on performance. Flowserve's products are compact, modular-built, high performance packages that are optimized for exact control and costeffective continuous operation. They have an extremely long life span as all parts are of highest quality. And they'll still be safe in the future as they use advanced technology and innovative solutions. Flowserve ensures a safe and cost-effective operation for our customers all over the world



Valtek ShearStream HP





Applications

High capacity, large turndown, moderate pressure drops, economical usage High flow rates based on unrestricted straight-through port

General Services

- When Globe- or Butterfly Valves are not suitable
- Chemical Industry general services
- Petrochemical Industry high temperatures, low emissions
- General Industries Water, Oil, Gas

More Severe Services

- Abrasive, erosive and corrosive applications
- Slurry, 2-phase Flow
- Liquid or pneumatic conveying
- Pulp, ash sluice water, plastic granules etc.

Valtek Positioner Options





XL

Extreme accuracy dual-stage analog, electropneumatic / pneumatic positioner. Explosionproof or Intrinsically safe.

Logix 500si Series

Economical compact user friendly digital positioner. With or without communication. Intrinsically safe.

Logix 3000IQ Series

Full-featured double acting, high volume digital positioner with HART or Foundation Fieldbus communication. Explosionproof or Intrinsically safe.



Valtek ShearStream SB

The excellent control characteristic of ShearStream SB are particularly beneficial in general control conditions found in the Process- and Chemical Industry. This is a default choice for standard applications, standard material selections and for moderate pressure ratings

Features

- Direct mounting of Turnex actuator
- One piece body
- Multiple packing options
- Tight shut-off
- Seat options
- Easy maintenance
- Characterized Ball Sector

Specification

Material	Carbon Steel (WCB) Stainless Steel (CF8M)
Sizes	ANSI 1" to 20" DIN DN25 to DN500
Pressure Classes	ANSI Class 150 to Class 300 DIN PN10 to PN40
End Connections	Flanged ANSI 1" to 20" / DIN DN25 to DN500 Wafer ANSI 1" to 8" / DIN DN25 to DN200



Options

ShearStream SB with Z-Trim

Works perfectly for steam regulation. ShearStream SB-Z can be used in a wide variety of applications and meets the highest demands for control accuracy.



The unique Z-Trim design reduces noise and avoids cavitation by taking the pressure drop in several steps. The Z-trim is self-cleaning so it can also be used with slurries.

Environmental Packing

SafeGuard packing set is an approved , tested and certified packing arrangement in accordance with ISO 15848-1.

Turnex - Actuator package

Heavy duty actuator for high performance control. Turnex has a swing-link mechanism for scotchyoke torque characteristics with no back-lash. Available as single- and double acting, fail open or fail close.

Direct mounted to Valve, Positioner, Solenoid Valves, Limit Switches.

Compact actuator with low mass for easy mounting.

Maintenance free for a long life

- Integrated air channels.
- Splines for different stem diameters.
- Torque range of 100 20.000 Nm at 5 bar.





Valtek ShearStream HP

"Robust" describes Valtek ShearStream HP Segmented Ball Valve. Designed to overcome the problems of harsh, particle entrained processes, ShearStream HP also provides accurate, reliable control in a broad range of applications such as chemical, power and petro-chemical.

Features

- One piece body
- Segmented V-notch ball
- Heavy duty seat option
- Bi-directional flexible metal seat
- Flanged or wafer bodies
- Designed for higher pressure classes



Specification

Material	Carbon Steel (WCB) Stainless Steel (CF8M) Other Alloys (Monel, Hastelloy B/C, Alloy 20, Titanium etc.)
Sizes	ANSI 1" to 16"
Pressure Classes	ANSI Class 150 to Class 600
End Connections	Flanged , Wafer

Seat Options

Flexible Metal Seat


The flexible metal seat uses the pressure drops across the seal to enhance its shut-off characteristics in both directions.

Soft Seat

The Soft Seat utilizes PTFE or PEEK soft seat inserts. The soft seat is also available with a metal back-up seal.



For applications requiring high pressure drops, the heavy duty seat provides tight shut-off and reliability. The sealed wave spring gives the seat consistent seating pressure that is longlasting. The soft seat option for the Heavy Duty seat utilizes an UHMWPE insert.



Valtek – Spring Cylinder Rotary Actuator

The Valtek spring cylinder rotary actuator combines high torque and pneumatic stiffness with excellent throttling capabilities. These characteristics are designed into a lightweight, robust and compact assembly, making the Valtek rotary actuator the foremost choice for ShearStream HP.







Your contact:



FCD VLEEBR0027-01 01.11

All data subject to change without notice.

© 10.2007 Flowserve Corporation. Flowserve and Valtek are trademarks of Flowserve Corporation

Flowserve Corporation

Flow Control 1350 N. Mt. Springs Parkway Springville, UT 84663 USA Phone: +1 801 489 8611 Fax: +1 801 489 3719

Flowserve (Austria) GmbH

Control Valves - Villach Operation Kasernengasse 6 9500 Villach Austria Phone: +43 (0)4242 41181 0 Fax: +43 (0)4242 41181 50

Flowserve India Controls Pvt. Ltd

Plot # 4, 1A, E.P.I.P, Whitefield Bangalore Kamataka India 560 066 Phone: +91 80 284 10 289 Fax: +91 80 284 10 286

Flowserve Essen GmbH

Manderscheidtstr. 19 45141 Essen Germany Phone: +49 (0)201 8919 5 Fax: +49 (0)201 8919 662

Flowserve S.A.S.

7, Avenue del la Libération - BP 60 63307 Thiers Cedex France Phone: +33 (0)4 73 80 42 66 Fax: +33 (0)4 73 80 14 24

NAF AB

Gelbgjutaregatan 2 SE-581 87 Linköping Sweden Phone: +46 (0)13 31 61 00 Fax: +46 (0)13 13 60 54

flowserve.com