




HHPX

End-suction, single-stage, radially split pump



Lower energy and maintenance costs

The Flowserve HHPX end-suction, single-stage, radially split pump is designed for high suction pressure seawater reverse osmosis (SWRO) desalination applications, such as energy recovery device (ERD) boosters. It is specifically engineered to deliver increased efficiency and easy maintenance, helping desalination plants lower energy and maintenance costs.

Improve efficiency and downtime

Back pullout design shortens maintenance times and enables service without disturbing motor or casing connections.

High suction pressure design is ideally suited for SWRO desalination operations.

Fan-cooled, oil-lubricated bearings withstand high suction pressures found in desalination operations.

Fully shrouded, precision-cast impellers and single- or dual-volute design increase pump efficiency.

Non-metallic wear rings reduce volumetric losses and increase efficiency.

Operating parameters

- Flows up to 4,000 m³/h (17,611 gpm)
- Heads to 70 m (230 ft)
- Pressures to 90 bar (1,305 psi)
- Temperatures: 50°C (122°F)
- Available in discharge sizes ranging from 8 to 20 in.



Optional instrumentation



The HHPX pump is compatible with advanced internet of things (IoT) solutions such as RedRaven condition monitoring from Flowserve. Flowserve RedRaven IoT solutions give you the insights and

tools you need to monitor, analyze and predict equipment performance — so you can improve pump uptime while reducing maintenance and energy costs.



Ask your Flowserve representative about optional RedRaven IoT monitoring packages or visit flowserve.com/iot to learn more.

Flowserve Corporation
5215 North O'Connor Blvd.
Suite 700
Irving, Texas 75039-5421 USA
Telephone: +1 937 890 5839

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2022 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.

PUFLY000138-02 (EN/AQ) May 2022