

		1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"
IPS-Welded and Seamless Pipe ANSI 1336.19 Stainless and ANSI 31.10 (Carbon and Alloy)															
Sch 5s	OD	—	—	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.563	6.625	8.625
	ID	—	—	.710	.920	1.185	1.530	1.770	2.245	2.709	3.334	4.334	5.345	6.407	8.407
Sch 10s	OD	.540	.675	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.563	6.625	8.625
	ID	.410	.545	.674	.884	1.097	1.442	1.682	2.157	2.635	3.260	4.260	5.295	6.357	8.329
Sch 40, 40s and Standard	OD	.540	.675	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.563	6.625	8.625
	ID	.364	.493	.622	.824	1.049	1.380	1.610	2.076	2.469	3.068	4.026	5.047	6.065	7.981
Sch 80, 80s Extra Strong	OD	.540	.675	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.563	6.625	8.625
	ID	.302	.423	.546	.742	.957	1.278	1.500	1.939	2.323	2.900	3.826	4.813	5.761	7.625
Sch 160	OD	—	—	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.563	6.625	8.625
	ID	—	—	.466	.614	.815	1.160	1.338	1.689	2.125	2.624	3.438	4.313	5.189	6.813
Double Extra Strength	OD	—	—	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.563	6.625	8.625
	ID	—	—	.252	.434	.599	.896	1.100	1.503	1.771	2.300	3.152	4.063	4.897	6.875
OD															
		(18Ga.) (16Ga.) (16Ga.) (16Ga.) (16Ga.) (16Ga.) (14Ga.) (14Ga.) (12Ga.) (12Ga.) (12Ga.)													
OD Tube Size	OD	—	—	—	.750	1.000	1.250	1.500	2.000	2.500	3.000	4.000	5.000	6.000	8.000
	ID	—	—	—	.652	.870	1.120	1.370	1.870	2.370	2.834	3.834	4.782	5.782	7.782
Copper Water Tube															
Type K	OD	.375	.500	.625	.875	1.125	1.375	1.625	2.125	2.625	3.125	4.125	5.125	6.125	8.125
	ID	.305	.402	.527	.745	.995	1.245	1.481	1.959	2.435	2.907	3.857	4.805	5.741	7.583
Type L	OD	.375	.500	.625	.875	1.125	1.375	1.625	2.125	2.625	3.125	4.125	5.125	6.125	8.125
	ID	.315	.430	.545	.785	1.025	1.265	1.505	1.985	2.465	2.945	3.905	4.875	5.845	7.725
Type M	OD	—	.500	.625	.875	1.125	1.375	1.625	2.125	2.625	3.125	4.125	5.125	6.125	8.125
	ID	—	.450	.569	.811	1.055	1.291	1.527	2.009	2.495	2.981	3.935	4.907	5.881	7.785
SPS Copper and Red Brass Pipe															
Regular	OD	.540	.675	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.562	6.625	8.625
	ID	.376	.495	.626	.822	1.063	1.368	1.600	2.063	2.501	3.062	4.000	5.062	6.125	8.001
Extra Strong	OD	.540	.675	.840	1.050	1.315	1.660	1.900	2.375	2.875	3.500	4.500	5.562	6.625	8.625
	ID	.294	.421	.542	.736	.951	1.272	1.494	1.933	2.315	2.892	3.818	4.812	5.751	7.625
Std Port Full Port	ID	.438	.438	.438	.563	.813	1.000	1.250	1.500	2.000	2.500	3.250	—	4.375	5.688
	ID	.438	.438	.563	.813	1.000	1.250	1.500	2.000	—	3.250	—	—	—	—
Econ-o-miser															
TE Bore	—	.378	.504	.628	.878	1.128	1.378	1.629	2.129						
SW Bore	—	.555	.690	.855	1.065	1.330	1.675	1.915	2.406						
BW Bore	—	.344	.516	.625	.812	1.047	1.375	1.594	2.062						
SWO Bore	—	—	—	.510	.760	1.010	1.260	1.510	2.010						

