

Scienco[™] SEM-100 and SEM-100FT

Fixed mounting and flow-through electronic flow meters



Accurate metering made simple

Scienco SEM-100 and SEM-100FT electronic flow meters employ positive displacement nutating disk technology to meter liquids of various viscosities with great accuracy and nominal pressure loss. With the largest LCD display available on the market, positive touch buttons and simple one-touch operation, the SEM-100 and SEM-100FT flow meters are easy to read and to use.

Two models

The SEM-100 meter mounts directly to the pump discharge via a 25 mm (1 in.) rear port. The flow-through configuration of the SEM-100FT enables the meter to be mounted at the hose end.

Features and benefits

Fixed mounting or flow-through configurations provide application flexibility.

Positive displacement nutating disk design meters liquids of various viscosities with great accuracy

and minimal pressure loss.

Simple, one-touch operation with large, positive touch buttons

LCD display measures 20 mm (0.75 in.), is the largest on the market, and features an anti-glare screen with back light.

Choice of three calibration modes to suit application needs

Extended battery life is provided by two AAA batteries.

Applications

- Agriculture
- Chemical transfer
- Non-flammable liquids
- Light oils
- Inks
- Automotive fluids

Operating parameters

- Flows from 0.5 to 6.8 m³/h (2 to 30 gpm)
- Temperatures to 55°C (130°F)
- Pressures to 4 bar (60 psi)
- Accuracy to +/- 0.5%
- Totals to 999,999



Scienco[™] SEM-100 and SEM-100FT

Materials of construction

Component	Material
Meter housing	Nylon [®] ; Polypropylene optional
Meter chamber	Polyphenylene sulfide (PPS) and stainless steel
O-rings	Viton [®] ; EPDM optional
Electronics body	Nylon

Note: Ensure chemical compatibility between liquid metered and the meter's wetted parts prior to use.

® Nylon and Viton are registered trademarks of the DuPont Company.

SEM-100FT flow-through flow meter with ball valve and spout

Headquarters

Flowserve Corporation 5215 North O'Connor Blvd. Suite 700 Irving, Texas 75039-5421 USA Telephone: +1-937-890-5839 Flowserve Corporation 3900 Cook Blvd. Chesapeake, VA 23323-1628 USA Telephone: +1-800-343-7867 (+1-800-343-PUMP) Fax: +1-757-673-3528 Email: csb@flowserve.com

PUFLY000700-01 (EN/AQ) September 2022

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

ON

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2022 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.